

Analogue Desktop Telephones

# Baseline Pro CLI terminal



Delivering a host of user-friendly features the analogue Baseline Pro CLI telephone matches your telephony networking requirements both in reliability and durability.

The slim design with small foot print will fit perfectly for a wide range of business communication requirements.

## At a glance

- > Easy to use
- > Speaker Phone
- > CLI
- > Message waiting lamp
- > Last number redial
- > Hold button
- > Yellow hold key for access to PBX transfer facilities



## Features

Called number display	+
Calling number display	+
Callers list	80
Callers list key	+
Direct memory keys	8
Earth recall	+
Hands-free mode	+
Hold	+
Last number redial	+
Line Power	+
Listen-in	+
Memory back-up	+
Message waiting LED	+
Optional desk stand	+
Pause insertion	+
Post-dialling DTMF	+
Pulse dialling	+
Ringer LED	+
Ringing tone selection	+
Speaker volume control	+
Time & call duration	+
Time-break recall	+
Timer key	+
Tone dialling	+
Wall mounting	+

## Technical Data

### Physical characteristics

- Size: 160 x 205 x 73 mm (w x d x h)
- Weight: BaseLine Pro CLI 700 g
- Colour: dark grey/charcoal

### Packaging

- Box size: 220 x 240 x 66 (w x d x h)

### Environmental conditions

- Temperature range:
  - rated -5° C to +45° C
  - transport -15° C to +55° C
- Relative humidity:
  - rated 10% to 90% RH
  - transport 5% to 95% RH

### Operating conditions

- The BaseLine Pro CLI range is line powered
- Up to 2 sets can be connected to one PBX port for BaseLine Pro CLI. This is reduced to 1 if message waiting is enabled on the set
- Two types of message waiting indication are supported for BaseLine Pro CLI
  - polarity reversal, activation voltage 20..60V, deactivation <2V
  - high voltage, activation voltage 85..120V, deactivation <65V
- Calling line identification compliant with the following standards are supported:
  - ETSI EN 300 659-1 V1.3.1 (2001-01)
  - ETSI EN 300 659-2 V1.3.1 (2001-01)
  - ETSI EN 300 659-3 V1.3.1 (2001-01)
- Transmission settings and voice quality are in compliance with the European telecom requirement TBR38

### Compatibility

- Operation is successfully verified on the SV9X00, SL1X00 and SIP@Net Server/iS3000 platforms

### Compliance

- European Directives & Standards
  - EMC: 2014/30/EU
  - LVD: 2014/35/EU
  - RoHS: 2011/65/EU
  - WEEE: 2012/19/EU
  - EMC: EN55024: 2010 / EN55032: 2012
  - Safety: EN60950-1:2006 + Amendments\*

\* EN60950-1:2006+A11:2009 +A1:2010+A12:2011+A2:2013

### Deliverables

The BaseLine Pro sets are supplied with:

- a line cord (3 m long with RJ11 plugs on both ends)
- a user guide
- a wall mounting bracket

For further information please contact NEC EMEA or:

EMEA (Europe, Middle East, Africa)  
NEC Enterprise Solutions  
[www.nec-enterprise.com](http://www.nec-enterprise.com)